



## Benefits of Single-Zone Duct-Free Split Mega 115V Wall-Mounted Systems

- Inverter technology
- Available in 9,000 and 12,000 Btu/h capacities
- 115 V electrical requirements
- All-season use—heat pump models for both cooling and heating capabilities
- Operating ranges for outdoor units of 14°F to 118°F (DB) for cooling; 14°F to 75°F (WB) for heating
- Operating ranges for indoor units of 64°F to 90°F (WB) for cooling; 60°F to 86°F (DB) for heating
- Quiet operation inside and out



### About LG Electronics, Inc.

LG Electronics, Inc. is a global leader and technology innovator in consumer electronics, mobile communications, and home appliances, employing more than 213,000 people in more than 60 countries worldwide. LG's commercial air conditioning business unit was established in 1968, and offers VRF, Multi F, duct-free split systems, packaged terminal air conditioners (PTACs), and room air conditioners.

***With LG, it's all possible.™***

# Mega 115V Wall-Mounted

## Single-Zone Duct-Free System

Duct-Free Split systems are comprised of two major components—indoor units and outdoor units—that are connected through refrigerant piping and power wiring / communications cable. These Inverter heat pump systems provide a smart alternative to both central HVAC and window-mounted air conditioners, and are available in a variety of configurations to suit different cooling and heating situations. Installation by a qualified HVAC contractor is easy—little to no duct work or sheet metal is required.

### Mega 115V Systems

Mega 115V Wall-Mount Split systems apply duct-free technology in a streamlined, low-profile design. Featuring an easier installation procedure and Inverter compressor technology, these systems are designed to save you time and money. Choosing a Mega 115V Wall-Mount split system provides a designer an edge with individual advanced control and design flexibility. Mega 115V Wall-Mount systems are available in nominal capacities of 3/4 and 1 ton. These are best suited for applications with zones that require heating or cooling, such as residential and small business office buildings.



### Inverter Technology

Inverter variable-speed split systems are measurably quieter and consume less energy than conventional air conditioners. The Inverter compressor ramps up or down to match the required room capacity and help maintain the comfort level. When the selected temperature is reached, the Inverter compressor operates at low speed to maintain that comfort level, thereby using less energy.

### Quality Commitment

LG is committed to the success of air-conditioning projects. We provide technical support during installation, and offer a variety of classes designed for installers and service providers. Classes are conducted at LG's training centers and in field locations at various times throughout the year and upon special request.

# Mega 115V Wall-Mounted Single-Zone Duct-Free Split Systems

## LS090HXV

8,500 Btu/h Cooling  
10,900 Btu/h Heating

## LS120HXV

12,000 Btu/h Cooling  
13,000 Btu/h Heating



### Features

- Inverter (Variable speed compressor)
- Gold Fin™ anti-corrosion
- 115V electrical requirements
- Cooling / Heating / Fan modes
- Jet Cool / Jet Heat
- Chaos Wind
- Four-Way Auto Swing
- Dehumidifying mode
- Auto operation / restart
- Condensate sensor connection
- Ultra quiet operation
- Includes handheld remote controller; wired wall-mounted controller available as an option (sold separately)

Warranty: Five (5) years parts; seven (7) years compressor.

\*Energy Star only applies to LS090HXV

System Model Number		LS090HXV*	LS120HXV
Indoor Unit Model Number		LSN090HXV	LSN120HXV
Outdoor Unit Model Number		LSU090HXV	LSU120HXV
Rated Cooling Capacity (Btu/h)		8,500	12,000
Rated Heating Capacity (Btu/h)		10,900	13,000
EER		12.01	10.50
SEER		17.0	17.0
HSPF		9.0	9.0
Air Circulation	CFM (H/M/L)	272 / 212 / 124	272 / 212 / 124
Fan Speeds		6 / 6 / 6	6 / 6 / 6
Dehumidification	pts. / hr.	2.3	2.8
Thermostat Range	Cooling (°F)	64 - 86	64 - 86
	Heating (°F)	60 - 86	60 - 86
Indoor Unit Sound Pressure Levels	dB(A) (H / M / L)	39 / 33 / 25	39 / 33 / 25
Outdoor Unit Sound Pressure Level	dB(A)	47	47
Power Supply (Outdoor and Indoor; Phase / V / Hz)		1 / 115 / 60	1 / 115 / 60
Indoor Unit Dimensions			
W x H x D	in.	34 27/32 x 11 1/4 x 8 9/32	34 27/32 x 11 1/4 x 8 9/32
Net Unit Weight	lbs.	23	23
Outdoor Unit Dimensions			
W x H x D	in.	28 1/4 x 19 1/32 x 9 1/16	28 1/4 x 19 1/32 x 9 1/16
Net Unit Weight	lbs.	67	67