

**KS30NKUA\*\* / KS36NKUA\*\***



**Indoor Unit**  
CS-KS30NKU / CS-KS36NKU



**Outdoor Unit**  
CU-KS30NKUA / CU-KS36NKUA



Wireless Controller (Included)



Wired Remote Controller CZ-RD515U controller CZ-RC515UA wire harness (Optional)



Wall Mount Air Conditioners				
Model No.		KS30NKUA		KS36NKUA
Unit Model No.		Indoor Unit	Outdoor Unit	Indoor Unit
		CS-KS30NKU	CU-KS30NKUA	CS-KS36NKU
			CU-KS36NKUA	CU-KS36NKUA
<b>Performance &amp; Electrical Ratings</b>				
Capacity	Cooling	Btu/h	30,600 (10,900-30,600)	
	Heating	Btu/h	---	
Moisture Removal	High	Pints/H	9.57	
	Hi / Med / Low	CFM	630 / 530 / 412	
SEER	Cooling		16.0	
EER	Cooling		9.3	
HSPF	Heating		---	
Power Supply		V, Phase, Hz	230 / 208V, 1PH, 60Hz	
Running Amps	Cooling	A	16.5 / 18	
	Heating	A	---	
Power Input	Cooling	W	3,290	
	Heating	W	---	
Back-up Heater		kW	---	
Fuse or Circuit Breaker Capacity		A	35	
<b>Features</b>				
Controls			Microprocessor	
Low Ambient Control			Built-in 0°F	
Wireless Remote Controller			Included	
Wired Remote Controller (optional)			CZ-RD515U & CZ-RC515UA	
Fan Speeds			Hi / Me / Lo & Auto	
Timer			1-hr OFF and 24-hr Program	
Air Deflection	Horizontal		Manual	
	Vertical		Automatic	
Air Filter			Washable	
Refrigerant			R-410A	
Refrigerant control			Electric Expansion Valve	
Operation Sound	In (Hi / Me / Lo / Qt)	dB-A	49 / 44 / 39 / 32	
	Outdoor (Hi)	dB-A	55	
Refrigerant Piping	Type		Flare	
	Discharge	inches	3/8	
	Suction	inches	5/8	
Refrigerant Pipe Length		Ft.	Max. 164	
Elevation Difference**	Outdoor Above	Ft.	Max. 100	
	Outdoor Below	Ft.	Max. 50	
<b>Dimensions &amp; Weight</b>				
Height		inches	Indoor Unit: 11-3/16	Outdoor Unit: 35-13/16
Width		inches	41-15/16	37-1/3
Depth		inches	9-1/16	13-3/8
Net Weight		Lbs.	32	183

Important: You must use refrigerant piping rated for R410a.

\*This is maximum elevation difference when the indoor unit is located above the outdoor unit. See p.45 for additional information.

\*\*Not for sale in CA, AZ, NV and NM.